



REAL POWER UNREAL PERFORMANCE

XSPowerBATTERIES.COM • 888.4XSPower



WE'VE UPDATED OUR
MOBILE APP, HAVE YOU?

Scan to download our new battery fitment and dealer locator app now or to browse our entire line of products

REAL POWER UNREAL PERFORMANCE

Check Out Our Entire Line of XS Power Mobile Audio Products at XSPOWERBATTERIES.COM

MAX Amps Explained: CA and CCA have been used since 1914 as a definition for battery performance. CA is defined as a measurement of the number of amps a 12V battery can deliver for 30 seconds at 32 degrees F and not drop below 7.2 volts. CCA is the same test at 0 degrees F. These tests were designed for the cars of yesteryear that had to be cranked for a long time to get started. Back then, CA and CCA numbers were very meaningful. However for mobile audio use, immediate burst output is more important. XS Power batteries when compared to the batteries of yesteryear deliver much more of their power quickly. This instant burst of energy we call "max amps".

SECONDARY WATTAGE INDICATOR



D375 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 800

CA : 190A RC : 25min Ah : 15

L: 7.67" (195.08mm)

W: 3.03" (76.90mm)

H: 5.28" (134.11mm)

Weight: 12.24lbs (5.55kg)

600Watts



D545 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 800

CA : 240A RC : 15min Ah : 14

L: 6.97" (177.04mm)

W: 3.38" (85.85mm)

H: 5.14" (130.50mm)

Weight: 11.01lbs (5.0kg)

600Watts



D680 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 1000

CA : 320A RC : 28min Ah : 20

L: 7.13" (181.1mm)

W: 3.03" (76.96mm)

H: 6.57" (166.88mm)

Weight: 15.42lbs (7.0kg)

1000Watts



D925 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2000

CA : 550A RC : 48min Ah : 28

L: 6.5" (165.1mm)

W: 6.93" (176.02mm)

H: 4.82" (124.96mm)

Weight: 23.54lbs (10.7kg)

2000Watts



D975 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2100

CA : 525A RC : 50min Ah : 35

L: 7.63" (193.93mm)

W: 5.3" (134.62mm)

H: 6.67" (169.42mm)

Weight: 26.43lbs (12kg)

2000Watts



D1200 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 2600

CA : 725A RC : 80min Ah : 44

L: 7.8" (198.12mm)

W: 6.54" (166.12mm)

H: 6.89" (175.02mm)

Weight: 33.25lbs (15.1kg)

3000Watts



D5100 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 3100

CA : 745A RC : 100min Ah : 60

L: 9.04" (229.62mm)

W: 5.43" (137.92mm)

H: 8.19" (208.03mm)

Weight: 39.60lbs (18kg)

3000Watts



D3400 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 3300

CA : 1000A RC : 135min Ah : 65

L: 10.24" (260.1mm)

W: 6.75" (171.4mm)

H: 7.20" (182.87mm)

Weight: 45.0lbs (20.85kg)

4000Watts



D2400 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 3300

CA : 670A RC : 150min Ah : 70

L: 10.24" (260.1mm)

W: 6.65" (168.91mm)

H: 8.31" (211.07mm)

Weight: 62.17lbs (28.3kg)

4000Watts



D6500 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 3900

CA : 1070A RC : 150min Ah : 75

L: 11.80" (299.72mm)

W: 7.20" (182.87mm)

H: 6.80" (172.72mm)

Weight: 58lbs (26.3kg)

4000Watts



D2700 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 4300

CA : 1170A RC : 185min Ah : 100

L: 12.09" (307.08mm)

W: 6.65" (168.91mm)

H: 8.31" (211.07mm)

Weight: 70.99lbs (32.2kg)

4500Watts



D3100 / 12V AGM

12 Volt High Performance AGM Power Cell

MAX AMP : 5000

CA : 1360A RC : 237min Ah : 110

L: 12.99" (329.95mm)

W: 6.81" (172.97mm)

H: 8.43" (214.12mm)

Weight: 75.40lbs (34.2kg)

5000Watts



D7500 / 12V AGM
 12 Volt High Performance AGM Power Cell
MAX AMP : 6000
 CA : 1700A RC : 280min Ah : 140
 L: 12.90" (328mm)
 W: 7.20" (183mm)
 H: 10.75" (273mm)
 Weight: 99.8lbs (45.26kg)
 7500Watts

NEW FROM XSPower

D4700, D4800, D4900 & D7500

The new additions to our D Series line-up include three direct fit European models, as well as the massive D7500, our largest and most powerful battery.



D4700 / 12V AGM
 12 Volt High Performance AGM Power Cell
MAX AMP : 2900
 CA : 745A RC : 105min Ah : 50
 L: 9.48" (241mm)
 W: 6.93" (176mm)
 H: 7.48" (190mm)
 Weight: 42.19lbs (19.14kg)
 3000Watts



D4800 / 12V AGM
 12 Volt High Performance AGM Power Cell
MAX AMP : 3000
 CA : 815A RC : 120min Ah : 60
 L: 10.04" (278mm)
 W: 6.93" (176mm)
 H: 7.48" (190mm)
 Weight: 48.22lbs (21.87kg)
 3000Watts



D4900 / 12V AGM
 12 Volt High Performance AGM Power Cell
MAX AMP : 4000
 CA : 1075A RC : 168min Ah : 80
 L: 13.88" (353mm)
 W: 8.93" (227mm)
 H: 7.48" (190mm)
 Weight: 61.22lbs (27.77kg)
 4000Watts

14V / 16V POWER CELLS



D1400 / 14V AGM
 14 Volt High Performance AGM Power Cell
MAX AMP : 2400
 CA : 675A RC : 85min Ah : 50
 L: 10.24" (260.1mm)
 W: 6.75" (171.4mm)
 H: 7.20" (182.87mm)
 Weight: 43.56lbs (19.75kg)



D1600 / 16V AGM
 16 Volt High Performance AGM Power Cell
MAX AMP : 2400
 CA : 675A RC : 85min Ah : 50
 L: 10.24" (260.1mm)
 W: 6.75" (171.4mm)
 H: 7.20" (182.87mm)
 Weight: 46.18lbs (21.85kg)

BILLET AND STAMPED ALUMINUM HOLD DOWNS



511
 D690 stamped aluminum side mount box with window



527
 D925 stamped aluminum GM direct mount and universal mounting kit
 *Baseplate & hardware included



535
 D875 billet aluminum hold down



573
 D1400, 1600 & 3400 billet aluminum hold down

**GENUINE XS POWER
CHARGERS AND ACCESSORIES**



HF1215 *240V models available upon request
Compact High Frequency AGM IntelliChargers
15AMP Max Output. 12V, 14V and 16V Models Available



1004
16V AGM IntelliCHARGER - 20AMP Max Output



1005 *1005E model not shown, in 110V & 240V switchable
12V, 14V and 16V AGM IntelliCHARGER, Compatible 5A, 15A and 25A (25AMP Max Output), Three Charging Modes



PSC IntelliSUPPLY *15A, 30A and 60A Models Available
12V, 14V and 16V Compact High Frequency IntelliSUPPLY with AGM charge mode. 15A, 30A and 60A Models Available



555
I-Bar multiple top post and side terminal adapter



Fuses/Holder
ANL, 1/0 to 4AWG, Fuse Holder - Silver Finish and Clear Cover. 150A, 200A, 250A, 300A and 350A Fuses Available



XS Flex / True AWG

STRAND CT : 4,704 MATL : 100% OXYGEN FREE COPPER

The **XS Flex** line of power cable is XS Power's flagship power cable. It is available in **Blue (XSFLEX0BL-50)** and **Clear (XSFLEX0CL-50)** and in both 50' spools or in 1' increments. The **XS Flex** cable is 100% Pure Oxygen Free Tinned Copper Cable with a massive 4,704 strand count. Just like everything else XS Power does the **XS Flex** cable exceeds the industry CEA-2015 cabling standards and is True AWG cable. The high strand count and soft touch cable jacket allows the wire to be super flexible and easy to use in any installation. Both **XS Flex** cables are also available in a 1,862 strand count 4 AWG and 735 strand count 8 AWG.

XS FLEX

Blue 1/0 (XSFLEX0BL-50)
Clear 1/0 (XSFLEX0CL-50)

Blue 4 AWG (XSFLEX4BL-100)
Clear 4AWG (XSFLEX4CL-100)

Blue 8 AWG (XSFLEX8BL-250)
Clear 8 AWG (XSFLEX8CL-250)

Distributed by:



888.4XSPOWER
2847 John Deere Dr. #102
Knoxville, TN 37917

Please note that product specs are subject to change. For the most up-to-date information regarding any XS Power product, please refer to xspowerbatteries.com